




## POFIX-75 LIGHT

### Description

#### LlaËs themelor pÃ«rfundimtar

**Pofix 75-Light** Æ«shtÆ« njÆ« llaËs suvaje i fabrikuar pÃ«r trajtim mekanik. PÃ«rdoret pÃ«r mbulimin e mureve tÆ« brendshme nÆ« njÆ« shtresÆ«. Mund tÆ« shtrohen mure tullash, blloqe betoni, mure betoni, blloqe siporex etj. SipÆ«rfaqja e bazÆ«s duhet tÆ« jetÆ« e thatÆ«, pluhuri dhe vaji duhet tÆ« hiqen dhe duhet tÆ« plotÆ«sojÆ« standardet e ndÆ«rtimit.



#### PÃ«rgatitja dhe aplikimi Parametrat

Koha e aplikimit pas pÃ«rzierjes me ujÆ«	3-4 orÆ«.
Koha e tharjes sÆ« materialit	48 h.
TrashÆ«sia e aplikimit	1.7 mm.
Granulimi	0.7 mm.

**Përshkrimi dhe aplikimi Parametrat**

Konsumi 15 kg/m<sup>2</sup>.

Temperatura  
e ajrit dhe e sipërfaqes +5/+35°C

Ngjyrë

Qese kg 30

Sasia/paletë 42

**Date Created**

01.05.2023

**Author**

admin

POFIX