





## POFIX-90

### Description

#### LlaËs me bazë« gipsi

**Pofix 90** Æ«shtË« llaËs me gips, gÆ«lqere dhe primer aditiv pÆ«r aplikim me makinË« dhe me dorË«. PÆ«rdoret si llaËs bazë« pÆ«r pÆ«rfundimin e llaËsit me pÆ«rmbajtje minerali, llaËs strukturor dhe llaËs rrÆ«shqitË«s. Aplikohet nÆ« mure tÆ« brendshme, tulla, blloqe betoni, sipÆ«rfaqe betoni tÆ« ashpÆ«r, tavane etj. PÆ«rdorimi i Pobetonconactit Æ«shtË« thelbÆ«sor nÆ« sipÆ«rfaqet e lÆ«muara tÆ« betonit.



#### PÆ«rgatitja dhe aplikimi Parametrat

Koha e aplikimit pas pÆ«rzierjes me ujË«	/
Koha e tharjes sÆ« materialit	24 h.
TrashË«sia e aplikimit	18 mm.
Granulimi	0-1,3 mm.

---

**Përshkrimi dhe Parametrat**

Konsumi 15 kg/m<sup>2</sup>.

Temperatura  
e ajrit dhe e sipërfaqes +5/+35°C

Ngjyrë

Qese kg 30

Sasia/paletë 42

**Date Created**

01.05.2023

**Author**

admin

POFIX